



MSA 315自动电熔焊机

MSA 315 自动电熔焊机结合了性能和紧凑的优化设计，用于民用和燃气/水行业的分布应用，焊接直径可达315mm的管件。此设备使用极其简单，操作人员只需几个基本步骤：连接、确认、扫描和开始焊接。用户需要时也可追溯焊工和工单号。

该焊机坚固耐用、安全且符合人体工程学，可靠适用于苛刻的条件。

根据环境温度自动进行能量输出补偿及冷却时间清晰显示，让整个焊接过程获得连续监控和调节。

内部存储器可存储达500个焊接报告，用户可导出至USB存储器后以PDF格式打印。

标准配置包含：1对4.0 mm的弯头适配器，说明书和选配的运输箱

技术参数：

- 环境温度：-10°C to 45°C
- 焊接参数输入方式：条码，手动
- 焊接技术：电压控制
- 主电压和频率：230V (190V - 265V) ， 50-60Hz
- 熔接电压：8-42 V
- 熔接电流：70 A (最大)
- 焊接范围：d20-315 mm
- 内部存储容量：500个焊接报告
- 协议格式：PDF, CSV
- 保护级别：等级1 / IP 65
- USB 端口：Type A
- 主电缆：4 m / 焊接电缆：3 m
- 重量：17 kg
- 显示：图形 LCD，可调对比度

Description	code	weight (kg)
Manual mode, carton box	790 128 040	17,000
Transport box, automatic with barcode reader	790 128 042	17,000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>