



Filtre oblique, PN 16

- Temperature: max. 100°C (water, air, oil, etc.)
- Material: gunmetal, stainless steel, EPDM
- Connection: female thread

DN (mm)	GN (inch)	Pouces (inch)	JRG Code	GF Code	SP	poids (kg)
10	3/8	3/8	1812.160	350 872 102	1	0,200
15	1/2	1/2	1812.240	350 870 902	1	0,340
20	3/4	3/4	1812.320	350 871 002	1	0,520
25	1	1	1812.400	350 871 102	1	0,575
32	1 1/4	1 1/4	1812.480	350 871 202	1	0,950
40	1 1/2	1 1/2	1812.560	350 871 302	1	1,290
50	2	2	1812.640	350 871 402	1	1,950
65	2 1/2	2 1/2	1812.720	350 871 502	1	2,900

DN (mm)	d1 Rp (inch)	d2 G (inch)	h1 (mm)	I (mm)	PN (bar)	z1 (mm)	z2 (mm)	µm
10	3/8	1/2	40	60	16	10	30	250
15	1/2	1/2	45	65	16	10	27	250
20	3/4	3/4	53	75	16	12	33	250
25	1	1	64	90	16	15	40	250
32	1 1/4	1 1/4	77	110	16	19	52	250
40	1 1/2	1 1/2	89	120	16	20	61	250
50	2	2	111	150	16	23	77	250
65	2 1/2	2 1/2	122	180	16	22	98	560

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>