



ecoFIT Segmented Bend 1.5D 60° PE100 SDR17

Model:

- Long spigot for butt- and electrofusion welding
- Production process: segment welded
- Application: Water distribution
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 8 bar water

Note:

* Please call us for availability

d (mm)	Code	Weight (kg)	Z (mm)	L (mm)	R (mm)	e (mm)	
90	P2314606090	0.73	254	150	180.0	5.4	
110	P2314606110	1.28	302	200	176.0	6.6	
125	P2314606125	1.68	308	200	187.5	7.4	
140	P2314606140	2.18	321	200	210.0	8.3	
160	P2314606160	2.98	339	200	240.0	9.5	
180	P2314606180	4.01	356	200	270.0	10.7	
200	P2314606200	5.16	373	200	300.0	11.9	
225	P2314606225	6.91	395	200	337.5	13.4	
250	P2314606250	10.03	467	250	375.0	14.8	
280	P2314606280	13.30	493	250	420.0	16.6	
315	P2314606315	21.26	623	350	472.5	18.7	
355	P2314606355	28.64	657	350	532.5	21.1	
400	P2314606400	38.19	696	350	600.0	23.7	
450	P2314606450	51.29	740	350	675.0	26.7	
500	P2314606500	71.18	833	400	750.0	29.7	
560	P2314606560	95.03	885	400	840.0	33.2	
630	P2314606630	134.90	996	450	945.0	37.4	
710	P2314606710	192.24	1115	500	1065.0	42.1	
800	P2314606800	295.03	1343	650	1200.0	47.4	
900	P2314606900	412.05	1479	700	1350.0	53.3	
1000	P2314606001	537.83	1566	700	1500.0	59.3	
*	1200	P2314606002	819.17	1739	700	1800.0	71.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>