



565型 蝶阀##凸耳式/美标法兰

裸轴

适用于ABS、PVC-U、PVC-C、ecoFIT、COOL-FIT和PROGEF系统

型号:




- 阀门结构长度符合标准: EN558 row 20, ISO 5752 row 20, API 609 table 2
- 满足标准法兰: ANSI/ASME B 16.5 Class 150, BS 1560: 1989 Class 125/150; BS 4504 PN10/16
- 安装简单, 易拆卸
- 适用于水和水处理应用 (例如海水、饮用水和工业用水)

选项:

- 可提供其他阀门配置
- GF可提供手动或电动执行器
- 可配阀位反馈器, 带LED指示
- 可选附件: 失效返回单元, 监测板, 定位器, Profibus DP板

注:

对于某些材料组合 (例如DN300阀门与PE/PP管道), 需要特殊的法兰适配器。请查看 www.gfps.com 上的“完美法兰连接工具”



d (mm)	DN (mm)	Size (inch)	PN (bar)	Acc.to ISO 5211	EPDM code	weight (kg)	FKM code	weight (kg)
63	50	2	16	F07	199 576 100	0,881	199 576 120	0,950
75	65	2 1/2	16	F07	199 576 101	1,115	199 576 121	1,217
90	80	3	16	F07	199 576 102	1,285	199 576 122	1,408
110	100	4	16	F07	199 576 103	2,024	199 576 123	2,200
140	125	5	16	F07	199 576 104	2,593	199 576 124	2,853
160	150	6	16	F07	199 576 105	3,743	199 576 125	3,791
225	200	8	10	F07	199 576 106	4,720	199 576 126	5,176
280	250	10	10	F10	199 576 107	8,837	199 576 127	9,517
315	300	12	6	F10	199 576 108	12,614	199 576 128	13,744

d (mm)	DN (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	V (mm)	V1 (mm)	Y (mm)	Lg (mm)	Q2 (mm)	k (mm)	d2 (mm)	D2 (mm)	H4 (mm)
63	50	230,4	84,8	140	133,3	70,1	27	43	28,3	120,7	UNC 5/8	155	23
75	65	247,7	84,8	161	139,9	80,8	27	46	43,8	139,7	UNC 5/8	175	23
90	80	263,9	84,8	180	145,6	91,3	27	46	63,5	152,4	UNC 5/8	190	23
110	100	288,6	84,8	211	166,4	106,2	16	52	83,7	190,5	UNC 5/8	221	23
140	125	316,3	84,8	239	180,0	120,3	16	56	110,4	215,9	UNC 3/4	250	23
160	150	340,4	84,8	263	189,0	132,4	19	56	137,3	241,3	UNC 3/4	277	23
225	200	388,8	84,8	319	209,5	160,3	19	60	191,1	298,5	UNC 3/4	337	23
280	250	201,6	125,0	403	262,5	199,1	40	68	238,9	362,0	UNC 7/8	403	23
315	300	559,8	125,0	482	284,3	235,5	40	78	285,5	431,8	UNC 7/8	479	23

d (mm)	DN (mm)	U (mm)	E (mm)	da1 (mm)
63	50	90	11	14,1
75	65	90	11	14,1
90	80	90	11	14,1
110	100	90	14	18,1
140	125	90	14	18,1
160	150	90	17	22,2
225	200	90	17	22,2
280	250	125	22	28,2
315	300	125	22	28,2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 2025/2/8



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>