




COOL-FIT 4.0 T90° reduced d75 – d225

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing



d	d1	D	D1	DN	SDR	PN	Code	Weight
(mm)	(mm)	(mm)	(mm)	(mm)		(bar)		(kg)
75	63	140	125	65	11	16	738 203 218	0.863
90	63	160	125	80	11	16	738 203 222	1.232
90	75	160	140	80	11	16	738 203 223	1.293
110	63	180	125	100	11	16	738 203 227	1.972
110	75	180	140	100	11	16	738 203 228	1.949
110	90	180	160	100	11	16	738 203 229	2.037
140	63	225	125	125	11	16	738 203 240	4.225
140	75	225	140	125	11	16	738 203 241	4.225
140	90	225	160	125	11	16	738 203 242	4.047
140	110	225	180	125	11	16	738 203 243	4.218
160	63	250	125	150	11	16	738 203 447	4.250
160	90	250	160	150	11	16	738 203 449	4.420
160	110	250	180	150	11	16	738 203 450	4.590
160	140	250	225	150	11	16	738 203 251	5.666
160	140	250	200	150	11	16	738 204 251	5.540
225	63	315	125	200	11	16	738 203 264	16.832
225	90	315	160	200	11	16	738 203 266	16.889
225	110	315	180	200	11	16	738 203 267	16.805
225	140	315	225	200	11	16	738 203 268	18.909
225	140	315	200	200	11	16	738 204 268	17.100
225	160	315	250	200	11	16	738 203 269	18.500

d	d1	D2	L	L1	L2	z	z1	Type
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
75	63	147	116	55	48	36	228.0	A
90	63	168	130	62	48	43	253.0	A
90	75	168	130	62	55	43	252.0	A
110	63	188	154	72	48	57	267.0	A
110	75	188	154	72	55	57	268.0	A
110	90	188	154	72	62	57	268.0	A
140	63	233	175	84	48	66	221.0	A
140	75	233	175	84	55	66	231.0	A
140	90	233	175	84	62	66	234.0	A
140	110	233	175	84	72	66	243.0	A
160	63	258	192	90	48	77	221.0	A
160	90	258	192	90	62	77	235.0	A
160	110	258	192	90	72	77	245.0	A
160	140	258	192	90	84	77	256.1	A
160	140	258	192	90	84	77	340.0	A
225	63	324	355	110	48	220	412.0	A
225	90	324	355	110	62	220	412.0	A
225	110	324	355	110	72	220	412.0	A
225	140	324	355	110	84	220	413.0	A
225	140	324	335	110	84	220	412.0	A
225	160	324	355	110	90	220	396.0	A

Data sheet

valid from: 1/25/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>