



MULTI/JOINT® 3207 Plus Wide Range end-cap blind, restraint, Uni/Fiksers

Model:

- Suitable for all kinds of pipe material
- Suitable for water
- Ductile Cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- EPDM gasket, EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the coupling range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) bolts, nuts and washers (optional: A4 quality)
- Hygiene protection included DN50 - DN600

Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- * DN350 & DN400 for plastic pipe materials = PN 10 bar water / MOP 5 bar gas

Note:

ID min. = minimum insertion depth

DN (mm)	Range 1 (mm)	NBR / A2 Code	weight (kg)	EPDM / A2 Code	weight (kg)	NBR / A4 Code	EPDM / A4 Code	weight (kg)
50	46 - 71	709 375 210	3.200	709 375 610	3.200	709 375 010	709 375 310	3.200
65	63 - 90	709 375 212	4.400	709 375 612	4.400	709 375 012	709 375 312	4.400
80	84 - 105	709 375 214	5.000	709 375 614	5.000	709 375 014	709 375 314	5.000
100	104 - 132	709 375 216	5.900	709 375 616	5.900	709 375 016	709 375 316	5.900
125	132 - 155	709 375 218	7.900	709 375 618	7.900	709 375 018	709 375 318	7.900
150	154 - 192	709 375 220	10.900	709 375 620	10.900	709 375 020	709 375 320	10.900
200	192 - 232	709 375 224	17.500	709 375 624	17.500	709 375 024	709 375 324	17.500
225	230 - 268	709 375 226	23.100	709 375 626	23.100	709 375 026	709 375 326	23.100
250	267 - 310	709 375 228	27.700	709 375 628	27.700	709 375 028	709 375 328	27.700
300	315 - 356	709 375 232	34.100	709 375 632	34.100	709 375 032	709 375 332	34.100
400	392 - 433	709 375 234	45.100	709 375 634	45.100	709 375 034	709 375 334	45.100

DN (mm)	a (mm)	b ID min. (mm)	e (mm)	PN Water (bar)	MOP Gas (bar)	
50	125 - 147	170	84	3xM12	16	8
65	133 - 156	191	84	3xM12	16	8
80	135 - 157	210	84	3xM12	16	8
100	143 - 169	241	90	3xM16	16	8
125	149 - 172	270	90	4xM16	16	8
150	169 - 206	312	110	4xM16	16	8
200	183 - 220	371	110	6xM16	16	8
225	216 - 254	415	125	6xM20	16	8
250	225 - 268	445	130	6xM20	16	8
300	238 - 276	495	130	8xM20	16	8
400	261 - 303	580	135	10xM20	16*	8*

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>