




Metering ball valve type 523 PVC-U
With mounting inserts/With solvent cement spigots metric

Model:


- Micro-doser
- Excellent control characteristics
- Designed for easy installation and removal
- Ball seals PTFE
- Angle of operation 180° with scale
- Integrated stainless steel mounting inserts
- Z-length, end connectors and union nuts compatible to Type 523

Option:


- Other materials on demand



d	DN	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
16	10	10	11	161 523 441	1	0.170	161 523 451	1	0.170
20	15	10	20	161 523 442	1	0.170	161 523 452	1	0.170



d	M1	M2	Lz1	Lz2	L	V1	H	Hmax	DE	BG	B3	H4	U
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)
16	35	47	28	28	114	27	72	99	50	M6	25	12	59
20	35	47	28	28	124	27	72	99	50	M6	25	12	59



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>