



PP Clamp saddle with female threaded double outlet

- Water PN16
- Suitable for PE and PVC Pipes
- Female thread: ISO 7 (parallel) / SS304
- Material: PP
- Gasket: O – ring with flat lip (EPDM)
- Bolt and nut: Galvanized / SS304 / SS316
- Colour: Blue
- Approval: WRAS

d
(mm)

63
75
90
110
125
140
160

SS304 Rp (inch) 1/2" Code	SS304 Rp 3/4" Code	SS304 Rp 1" Code	SS304 Rp 1/2 x 3/4" Code	SS304 Rp 1/2" x 1" Code	SS304 Rp 3/4" x 1" Code	Weight (kg)
300 211 622	300 211 623	300 211 624	300 211 625	300 211 626	300 211 627	0.316
300 211 628	300 211 629	300 211 630	300 211 631	300 211 632	300 211 633	0.394
300 211 634	300 211 635	300 211 636	300 211 637	300 211 638	300 211 639	0.484
300 211 640	300 211 641	300 211 642	300 211 643	300 211 644	300 211 645	0.561
300 211 646	300 211 647	300 211 648	300 211 649	300 211 650	300 211 651	0.863
300 211 652	300 211 653	300 211 654	300 211 655	300 211 656	300 211 657	0.933
300 211 658	300 211 659	300 211 660	300 211 661	300 211 662	300 211 663	1.007

GP	L	L1	H	H1
(mm)	(mm)	(mm)	(mm)	(mm)
30	61	102	192	18.0
25	78	124	216	19.5
20	86	137	244	19.5
30	98	154	286	18.0
25	110	174	316	20.0
20	118	194	346	19.5
20	124	214	388	20.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>