




ELGEF Plus Electrofusion coupler PE100
d355-800mm / SDR11

- 10 bar Gas / 16 bar Water
 - 4 mm pin connectors
 - Limited path fusion indicators
 - With active reinforcement
 - Ø355 – 500 have two connected (monofilar) welding zones (Both pipe ends can be welded simultaneously)
 - Ø560 – 800 have two separate (bifilar) welding zones (Both pipe ends can be welded separately)
- * FM 1613 approved - 15 bar



	d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)	Do (mm)	Lmax (mm)	SDR pipe
*	355	350	16	753 911 704	13.098	438	291	9-17
*	400	400	16	753 911 705	18.320	493	295	9-17
*	450	450	16	753 911 706	24.700	554	327	9-17
*	500	500	16	753 911 707	33.700	616	358	9-17
	560	600	16	753 911 708	46.200	689	396	9-17
	630	600	16	753 911 709	65.300	775	440	9-17
	710	700	16	753 911 710	97.400	874	463	9-17
	800	800	16	753 911 711	114.500	982	484	9-17

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>