



Guided Radar Level Transmitter 2291

Remark:

Display: Graphical LCD, adjustable contrast
Sensor Type cable/rod

MFR #	Description	Measuring range (m)	Connection
2291-S-1DB1X-6-R	Main cable: 19.69 ft (6 m)	0.2 - 6.0	1" BSP
2291-S-1DN1X-6-R	Main cable: 19.69 ft (6 m)	0.2 - 6.0	1" NPT
2291-S-1DB1X-2-D	6.56 ft(2m) rod, 0.315 in (Ø 8mm)	0.2 - 2.0	1" BSP
2291-S-1DN1X-2-D	6.56 ft(2m) rod, 0.315 in (Ø 8mm)	0.2 - 2.0	1" NPT

MFR #	Code	SP	weight (kg)
2291-S-1DB1X-6-R	159 300 198	1	0.790
2291-S-1DN1X-6-R	159 300 199	1	0.790
2291-S-1DB1X-2-D	159 300 204	1	0.790
2291-S-1DN1X-2-D	159 300 205	1	0.790

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>