



INSTAFLEX Adapter PB/Brass Socket fusion transition to loose nut adapter concerning / Flat seal

Socket fusion transition to loose nut adapter concerning
Thread in DZR brass, UBA (Umwelt Bundesamt, Germany) conform
EPDM sealing hot and cold water approved
Incl. flat seal EPDM
*as long as stock last

d	G	Code	SP	Weight	L	z	k max.
(mm)	(inch)			(kg)	(mm)	(mm)	(mm)
16	¾	761 069 684	1	0.715	100	93	22
20	¾	761 069 685	1	0.158	102	94	24
20	1	761 069 686	1	0.171	107	98	24
25	¾	761 069 687	1	0.171	108	101	23
25	1	761 069 688	1	0.211	110	102	23
25	1 ¼	761 069 689	1	0.274	118	109	23
32	1	761 069 690	1	0.260	118	110	21
32	1 ¼	761 069 691	1	0.289	118	110	21
32	1 ½	761 069 692	1	0.358	119	110	21
40	1 ¼	761 069 693	1	0.378	134	105	24
40	1 ½	761 069 694	1	0.402	132	124	24
*	40	2 761 069 695	1	0.576	139	126	24
50	1 ¾	761 069 696	1	0.607	142	131	22
50	2 ¼	761 069 697	1	0.705	150	138	22
63	2 ¾	761 069 698	1	1.051	159	147	21
*	63	2 ¾ 761 069 699	1	1.177	161	146	21
*	16	½ 761 069 700	1	0.125	98	91	22
*	20	¾ 761 069 701	1	0.116	102	95	24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>