



Profile Flange Gasket EPDM/FKM metric

Model:

- For all metric GF Flange Adaptors
- Profile Gasket with steel insert (type G-ST-P/K)
- Hardness: 70° Shore EPDM, 75° Shore FKM
- **EPDM:** approved acc. to DVGW W 270, KTW recommendation
- Dimension D is in accordance with the centering on the inner diameter of the bolt circle.
- material steel insert: carbon steel

di FA are the suitable inner diameters of flange adaptors

d (mm)	PN (bar)	DN (mm)	EPDM Code	FKM Code	weight (kg)	D (mm)	D1 (mm)	H (mm)	H1 (mm)	di FA (mm)
16	16	10	748 440 705	749 440 705	0.012	46	16	4	3	6 - 16
20	16	15	748 440 706	749 440 706	0.013	51	20	4	3	10 - 20
25	16	20	748 440 707	749 440 707	0.014	61	22	4	3	12 - 22
32	16	25	748 440 708	749 440 708	0.019	71	28	4	3	18 - 28
40	16	32	748 440 709	749 440 709	0.026	82	40	4	3	30 - 40
50	16	40	748 440 710	749 440 710	0.039	92	46	4	3	36 - 46
63	16	50	748 440 711	749 440 711	0.050	107	58	5	4	48 - 58
75	16	65	748 440 712	749 440 712	0.082	127	69	5	4	59 - 69
90	16	80	748 440 713	749 440 713	0.083	142	84	5	4	73 - 84
110	16	100	748 440 714	749 440 714	0.127	162	104	6	5	94 - 104
125	16	100	748 440 715	749 440 715	0.105	162	123	6	5	113 - 123
140	16	125	748 440 716	749 440 716	0.173	192	137	6	5	127 - 137
160 - 180	16	150	748 440 717	749 440 717	0.207	218	160	8	6	150 - 160
200	16	200	748 440 719	749 440 719	0.263	273	203	8	6	192 - 203
225	16	200	748 440 720	749 440 720	0.255	273	220	8	6	207 - 220
250	16	250	748 440 721	749 440 721	0.462	328	252	8	6	238 - 252
280	16	250	748 440 722	749 440 722	0.323	328	274	8	6	264 - 274
315	16	300	748 440 723	749 440 723	0.549	378	306	8	6	296 - 306
355	16	350	748 440 724	749 440 724	0.870	438	355	10	7	340 - 355
400	16	400	748 440 725	749 440 725	1.088	489	400	10	7	385 - 400
450	16	500	748 440 726	749 440 726	0.718	594	403	10	7	393 - 403
500	16	500	748 440 727	749 440 727	0.718	594	447	10	7	437 - 447
560	16	600	748 440 728	749 440 728	0.923	695	494	10	7	484 - 494
630	16	600	748 440 729	749 440 729	0.923	695	555	10	7	545 - 555

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>