



Kugelhahn Typ 375 PVC-U
Mit Stumpfschweisstützen lang
PE100 SDR11 metrisch

Ausführung:

- True double union safe block ball valve
- Kugeldichtung PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-dimension, valve end and union nut are not compatible with type 546

Einsatzbereich:

- Basic industrial applications without automation

d	DN	Zoll	PN	kv-Wert	EPDM	NPK	SP	Gewicht
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code			(kg)
				(L/min)				
20	15	½	16	185	161 375 542		1	0.141
25	20	¾	16	350	161 375 543		1	0.213
32	25	1	16	700	161 375 544		1	0.312
40	32	1 ¼	16	1000	161 375 545		1	0.474
50	40	1 ½	16	1600	161 375 546		1	0.761
63	50	2	16	3100	161 375 547		1	1.252
75	65	2 ½	10	5000	161 375 548		1	1.252
90	80	3	10	7000	161 375 549		1	3.518
110	100	4	10	11000	161 375 550		1	6.129

d	FKM	NPK	SP	Gewicht	D	H	L	L1	L2	L3	e
(mm)	Code			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	161 375 552		1	0.141	50	53	175	67	42	40	1.9
25	161 375 553		1	0.213	59	60	195	77	48	45	2.3
32	161 375 554		1	0.312	68	67	247	87	54	51	2.9
40	161 375 555		1	0.474	80	79	233	102	62	59	3.7
50	161 375 556		1	0.761	94	90	265	119	72	70	4.6
63	161 375 557		1	1.252	115	107	278	146	86	84	5.8
75	161 375 558		1	2.381	145	129	348	179	110	103	6.8
90	161 375 559		1	3.518	168	143	350	209	128	120	8.2
110	161 375 560		1	6.129	210	169	412	250	150	141	10.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>