






**NeoFlow Pressure reducing valve POM-C**  
**Maximum downstream pressure 195 psi (g)**

- Available dimensions: 8" – 12"
- Maximum upstream pressure: 232 psi (g)
- Connection type: Wafer Design
- Sealing material: EPDM
- Body material: POM-C
- Components: Stainless Steel
- Thread fittings: NPT
- Medium: Water
- Co-developed with OFUI



| Nominal Pipe Diameter | Maximum upstream pressure (psi(g)) | Maximum downstream pressure (psi(g)) | Code               | Weight (lb) |
|-----------------------|------------------------------------|--------------------------------------|--------------------|-------------|
| 8"                    | 232                                | 195.0                                | <b>193 174 420</b> | 57.3        |
| 10"                   | 232                                | 195.0                                | <b>193 174 422</b> | 76.7        |
| 12"                   | 232                                | 195.0                                | <b>193 174 423</b> | 156.5       |

| D      | Lmax   | Lb     | Hmax   | Wmax   |
|--------|--------|--------|--------|--------|
| (inch) | (inch) | (inch) | (inch) | (inch) |
| 10.8   | 11.73  | 11.73  | 15.98  | 19.09  |
| 12.9   | 13.70  | 13.70  | 20.08  | 21.65  |
| 14.9   | 15.67  | 15.67  | 23.46  | 25.20  |



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>