



PROGEF Plus silicone free Diaphragm valve type 317
With flanges metric


Model:

- Material: PP-H / silicone free cleaned
- DN 80-150 with fixed flange
- Overall length according to EN 558
- Connecting dimension: ISO 7005 / EN 1092 / DIN 25 PN10 / BS4504
- Double bagged
- Jointing surfaces: serrated or flat


*** DN80 and DN150 fixed flanges metric and inch ANSI B16.5**

	d	Size	DN	PN	kv-value	EPDM	PTFE with
	(mm)	(inch)	(mm)	(bar)	($\Delta p=1$ bar)	Code	EPDM
					(l/min)		supporting
							diaphragm
							Code
	75	2 1/2	65	10	992	167 317 218	167 317 233
*	90	3	80	10	1700	167 317 129	167 317 144
	110	4	100	10	2700	167 317 130	167 317 145
*	160	6	150	7	6033	167 317 132	167 317 147


	D	D1	D2	D3	H	H1	H2	L	L1	L2	L3	M	Lift =	AL
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		Hx	(mm)
	185	145	152	18	210	46	15	290		70		M8	35	4
*	200	160	270	18	265	57	23	310	35	120		M12	40	8
	225	180	270	18	304	69	23	350	38	120		M12	50	8
*	282	241	400	23	437	108	23	480	29	100	200	M12	70	8



DN 15-65



DN 80-100



DN 150

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>