



INSTAFLEX Valvola BVT 2 PB Senza scarico

- Materiale: PB, ottone, bronzo
 - Ottone: UBA conformarsi
 - Collegamento: Polifusione di tasca
 - Guarnizione: EPDM, omologata per acqua potabile calda e fredda
- * finché durano le previste

	d (mm)	code	NPK	SP	weight (kg)
*	20	761 070 304	481 712	1	0.379
*	25	761 070 305	481 713	1	0.370
*	32	761 070 306	481 714	1	0.387
*	40	761 070 307	481 715	1	1.099
*	50	761 070 308	481 716	1	1.151
*	63	761 070 309	481 717	1	1.492

	d (mm)	D (mm)	L (mm)	H (mm)	z (mm)	Value (Zeta)	kv-100-value ($\Delta p=1$ bar) (l/min)
*	20	55	40	112	25	0.4	421
*	25	55	40	112	22	0.4	421
*	32	55	43	112	23	0.4	421
*	40	90	55	165	33	0.3	1291
*	50	90	60	165	35	0.3	1291
*	63	90	75	165	47	0.3	1291

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>