



UNI-Combigrip S/S2 coupling stainless steel 1.4571
Tensile-resistant connection of metal and plastic
PN6 Solid bolt



Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating temperature EPDM: -30°C to 125°C
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton (FKM) on request

Remark:

For safe installation on PVC-, ABS-, PE-, PP- and PB-pipes insert stiffeners are mandatory

Attention:

- **The difference between the different pipe outside diameters OD1 < OD2 is 1% or max. 3 mm.**

OD nominal (mm)	EPDM Code	PF Weight (kg)	NBR Code	PF
172 - 185	779 750 924	5.0	779 747 924	1 D1 A90 220
195 - 208	779 750 925	5.4	779 747 925	1 D1 A90 220
215 - 228	779 750 926	5.8	779 747 926	1 D1 A90 220
247 - 260	779 750 927	6.5	779 747 927	1 D1 A90 220
269 - 282	779 750 928	6.9	779 747 928	1 D1 A90 220
312 - 325	779 750 929	8.6	779 747 929	1 D1 A90 220
350 - 363	779 750 930	9.5	779 747 930	1 D1 A90 220
395 - 408	779 750 931	13.5	779 747 931	1 D1 A90 220
447 - 460	779 750 932	17.5	779 747 932	1 D1 A90 220
502 - 515	779 750 933	19.3	779 747 933	1 D1 A90 220

OD nominal (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque maximal (N/m)
172 - 185	6	10	172	185	223	140	249	160
195 - 208	6	10	195	208	246	140	272	160
215 - 228	6	10	215	228	266	140	292	160
247 - 260	6	10	247	260	298	140	324	160
269 - 282	6	10	269	282	320	140	346	160
312 - 325	6	10	312	325	363	142	389	160
350 - 363	6	10	350	363	401	142	427	160
395 - 408	6	10	395	408	446	146	472	160
447 - 460	6	10	447	460	498	146	524	160
502 - 515	6	10	502	515	553	146	579	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>