



## Multi-pin plug, for all positioners type SPC, RPC

### Model:

- for electrical connection of positioner type SPC, type RPC to customer's control system
- Protection class IP67 / IP68 / IP69
- A-coded
- Connector angled
- free cable end
- Operating voltage max. 250 V AC/DC
- Operating current max. 4 A
- Microbe and hydrolysis resistant
- Halogen-free
- Ambient temperature
- Connector: -40 ... 90 °C (-40 ... 194 °F)
- Cable, fixed: -40 ... 80 °C (-40 ... 176 °F)
- Cable, movable: -25 ... 80 °C (-13 ... 176 °F)
- Pollution degree: 3

Description	Code
Round-plug M8 4-pol w. cable 5m PUR	<b>199 190 651</b>
Round-plug M12 8-pol w. cable 5m PUR	<b>199 190 649</b>
Round-plug M12 4-pol w. cable 5m PUR	<b>199 190 650</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>