



## ecoFIT installation fitting type 314 PE100

### Model:

- Threaded outlet 1 1/4" NPSM
- For conventional hot gas back welding according to DVS 2207 part 3

### Attention:

- pH sensors can also be used for dimensions above d180/DN150 and below d75/DN65 with 753 314 000. The length might have to be adjusted (sensor has to touch the medium)
- only for pressureless or low pressure application
- pressure rate depends on quality of hot gas back welding
- please consult the instruction manual
- Installation by trained and certified welders only
- sensor length depends on installation fitting

### Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

| d<br>(mm) | DN        | Code               | Weight<br>(kg) | D<br>(mm) | L<br>(mm) | Sensor Type    |
|-----------|-----------|--------------------|----------------|-----------|-----------|----------------|
| 65 - 150  | 65 - 150  | <b>753 314 000</b> | 0.040          | 37        | 68        | flow X0, pH XX |
| 200 - 350 | 200 - 350 | <b>753 314 001</b> | 0.057          | 37        | 102       | flow X1        |
| 350 - 600 | 350 - 600 | <b>753 314 002</b> | 0.934          | 37        | 178       | flow X2        |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>