



**MULTI/JOINT® 3057 Plus Wide Range Flange adaptor,
restraint, Uni/Fiksers acc. to AWWA C110**

Model:

- Suitable for all kinds of pipe material
- Suitable for water
- Ductile Cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- EPDM gasket, EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the coupling range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) bolts, nuts and washers (optional: A4 quality)
- Hygiene protection included DN50 - DN600

Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information

Note:

ID min. = minimum insertion depth

DN (mm)	DN (inch)	Range 1 (mm)	Range 1 (inch)	Flange 3 (mm)	Flange 3 (inch)
50	2	46 - 71	1.811 - 2.795	50	2
65	2 ½	63 - 90	2.480 - 3.543	65	2 ½
80	3	84 - 105	3.307 - 4.133	80	3
100	4	104 - 132	4.094 - 5.196	100	4
150	6	154 - 192	6.062 - 7.559	150	6
200	8	192 - 232	7.559 - 9.133	200	8
250	10	267 - 310	10.500 - 12.204	250	10
300	12	315 - 356	12.401 - 14.015	300	12
400	16	392 - 433	15.433 - 17.047	400	16
reduced	425	432 - 464	17.000 - 18.267	400	16
reduced	475	481 - 513	18.937 - 20.196	400	16

	NBR / A2 Code	EPDM / A2 Code	NBR / A4 Code	EPDM / A4 Code	weight (kg)
	709 355 211	709 355 611	709 355 011	709 355 311	4.700
	709 355 213	709 355 613	709 355 013	709 355 313	5.700
	709 355 240	709 355 640	709 355 040	709 355 340	6.700
	709 355 242	709 355 642	709 355 042	709 355 342	8.400
	709 355 244	709 355 644	709 355 044	709 355 344	14.200
	709 355 246	709 355 646	709 355 046	709 355 346	22.100
	709 355 248	709 355 648	709 355 048	709 355 348	32.600
	709 355 250	709 355 650	709 355 050	709 355 350	42.400
	709 455 294	709 455 694	709 455 094	709 455 394	86.900
reduced	709 455 289	709 455 689	709 455 089	709 455 389	72.100
reduced	709 455 291	709 455 691	709 455 091	709 455 391	81.100

a (inch)	b (inch)	ID min. (inch)	e (inch)	PSI Water (psi)	No. of bolt holes flange
6.496 - 7.362	6.457	3.307	3xM12	232	4
6.693 - 7.598	7.323	3.307	3xM12	232	4
6.693 - 7.559	8.031	3.307	3xM12	232	4
6.811 - 7.835	9.291	3.543	3xM16	232	8
8.307 - 9.764	11.969	4.331	4xM16	232	8
8.700 - 10.157	13.937	4.331	6xM16	232	8
10.394 - 12.087	17.008	5.118	6xM20	232	12

Data sheet

valid from: 1/25/25



	a (inch)	b (inch)	ID min. (inch)	e (inch)	PSI Water (psi)	No. of bolt holes flange
	11.535 - 13.032	19.488	5.118	8xM20	232	12
	11.693 - 13.465	20.630	5.315	10xM20	150	16
reduced	12.992 - 14.449	24.528	6.229	10xM20	150	16
reduced	14.173 - 15.630	26.457	6.229	10xM20	150	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>