


Gomito 45° PE 100 SDR17/17,6

- Gas 5 bar / Acqua 10 bar



d	DN	PN	code	NPK	weight	Lmax	Q1	s1	z
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
90	80	10	753 150 813	422 156	0.411	236.7	81	5.4	120
110	100	10	753 150 814	422 157	0.722	260.8	86	6.6	130
125	100	10	753 150 815	422 158	0.948	283.2	92	7.4	140
140	125	10	753 150 816	422 161	1.259	329.5	120	8.3	164
160	150	10	753 150 817	422 162	1.901	333.1	102	9.5	162
180	150	10	753 150 818	422 163	2.386	353.8	107	10.7	170
200	200	10	753 150 819	422 164	3.153	388.2	116	11.9	186
225	200	10	753 150 820	422 165	4.441	429.5	123	13.4	205
250	250	10	753 150 821	422 166	6.012	458.8	130	14.8	217
280	250	10	753 150 822	422 167	7.489	491.6	140	16.6	230
315	300	10	753 150 823	422 168	10.123	538.1	150	18.7	250

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>