





Vanne à bille type 375 PVC-U Avec emboîture pour collage métrique

Exécution:

- True double union safe block ball valve
- joint de la bille en PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- Cote z extrémités de la vanne et écrous incompatibles avec le type 546

Domaine d'utilisation

- Basic industrial applications without automation



d	DN	Pouces	PN	valeur kv	EPDM	SP	poids	FKM	SP	poids
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
75	65	2 1/2	10	5000	161 375 508	1	2,191	161 375 518	1	2,191
90	80	3	10	7000	161 375 509	1	3,303	161 375 519	1	3,303
110	100	4	10	11000	161 375 510	1	5,954	161 375 520	1	5,954

d	D	H	L	L1	L2	L3	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
75	145	129	206	179	110	103	118
90	168	143	242	209	128	120	140
110	210	169	282	250	150	141	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>