



## Positioner Type RPC, for rotary actuators

### Model:

- For pneumatic rotary actuators in single-acting and double-acting function
- Operation/configuration via DIP switch internal
- Supply voltage 24V DC
- Control signal 4-20 mA
- Conductive plastic rotary potentiometer as displacement transducer
- Electrical connection multi-pin plug (not included)
- Protection class IP65/IP67
- Binary input (fail-safe position, changeover)
- Operating status (automatic / manual)
- Analog feedback (0/4...20 mA) for setpoints and actual values
- Approved and listed according to cCSAus

### Option:

- Adaption for mounting on pneumatic actuator
- Multipole plug

Type	Code	Weight	Y4	W1	W2	L1	L2
		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
RPC	<b>199 190 640</b>	1.000	83.5	48	62	60.5	100.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>