




ELGEF Plus Tee 90° reduced PE100 d90-250mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- * Two separate fusion zones



d	d2	DN	PN	Code	Weight
(mm)	(mm)	(mm)	(bar)		(kg)
110	90	100	16	753 211 034	1.652
125	90	100	16	753 211 035	2.242
140	63	125	16	753 901 867	2.879
140	75	125	16	753 901 868	2.938
140	90	125	16	753 901 869	3.044
140	110	125	16	753 901 870	3.234
160	63	150	16	753 211 025	3.737
160	90	150	16	753 211 026	3.855
160	110	150	16	753 211 027	3.973
*	200	90	16	753 211 059	9.012
*	200	110	16	753 211 060	12.400
*	200	160	16	753 211 063	12.400
*	225	90	16	753 211 069	13.100
*	225	110	16	753 211 070	13.100
*	225	160	16	753 211 073	13.600
*	250	110	16	753 211 080	11.660
*	250	160	16	753 211 083	17.070

d	Do	L2	Lmax	P1	Z1	Q2	Suitable for
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
110	140	245	255	72	56	80	Pipe SDR 9-17.6
125	156	245	276	75	53	80	Pipe SDR 9-17.6
140	185	220	300	83	67	80	Pipe SDR 9-17.6
140	185	230	300	83	67	90	Pipe SDR 9-17.6
140	185	235	300	83	67	95	Pipe SDR 9-17.6
140	185	245	300	83	67	105	Pipe SDR 9-17.6
160	208	178	330	89	76	63	Pipe SDR 11-17.6
160	208	209	330	89	76	94	Pipe SDR 11-17.6
160	208	219	330	89	76	104	Pipe SDR 11-17.6
*	200	250	216	595	104	194	81 Pipe SDR 11-26
*	200	250	219	600	104	194	84 Pipe SDR 11-26
*	200	250	237	595	104	194	101 Pipe SDR 11-26
*	225	280	228	666	112	217	80 Pipe SDR 11-26
*	225	280	238	670	112	217	85 Pipe SDR 11-26
*	225	280	258	667	112	217	105 Pipe SDR 11-26
*	250	310	284	709	123	220	85 Pipe SDR 11-26
*	250	310	266	711	123	220	101 Pipe SDR 11-26

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 2/3/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>