





COOL-FIT 4.0 Übergangverschraubung PE/ABS

Ausführung:

- Einschraubteil: ABS Klebemuffe
- Einlegteil: Stutzenfitting PE100 SDR11, metrisch mit freiem Ende
- Gasket: O-ring EPDM Nr. 748 410 008-014
- Überwurfmutter ABS
- Einschliesslich Isolationshalbschalen



d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	NPK	Gewicht (kg)
32	134	25	11	10	738 513 708	454 112	0.169
40	143	32	11	10	738 513 709	454 113	0.256
50	154	40	11	10	738 513 710	454 114	0.334
63	172	50	11	10	738 513 711	454 115	0.522
75	210	65	11	10	738 513 712	454 116	0.996
90	233	80	11	10	738 513 713	454 117	1.336
110	263	100	11	10	738 513 714	454 118	1.900



D1 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	z1 (mm)	z2 (mm)
90	137	36	33	109	104	11
110	156	40	39	126	117	13
110	169	44	46	135	123	15
125	190	48	58	152	132	21
140	211	55	62	170	149	18
160	215	62	69	167	146	18
180	235	72	72	177	163	11

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>