



COOL-FIT 4.0 Elbow 45° d32-d225

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing

d	D	DN	SDR	PN	Code	Weight	D1	L	L1	z	Closest inch	Type
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(inch)	
32	90	25	11	16	738 153 108	0.108	97	72	36	11	1	A
40	110	32	11	16	738 153 109	0.162	117	76	40	11	1 ¼	A
50	110	40	11	16	738 153 110	0.218	117	82	44	13	1 ½	A
63	125	50	11	16	738 153 111	0.315	132	89	48	16	2	A
75	140	65	11	16	738 153 112	0.650	147	98	55	18	2 ½	A
90	160	80	11	16	738 153 113	1.030	168	117	62	30	3	A
110	180	100	11	16	738 153 114	1.270	188	138	72	41	4	A
140	225	125	11	16	738 153 116	2.958	233	157	84	48	5	A
160	250	150	11	16	738 153 117	4.100	258	161	90	46	6	A
225	315	200	11	16	738 153 120	17.603	324	278	110	143	8	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>