



COOL-FIT PE Plus Electric Actuated Butterfly valve Type 145, insulated

Model:

- ABS with spigot PE100 **SDR11**, metric
- Voltage 100-230V, 50-60Hz
- Factory set control range 90°<
- Basic position A-C opened, activated position B-C opened, see flow scheme
- Including valve, flange adaptors, and insulation half shells
- Separate Fittings type A needed for joining

d	DN	PN	Cv-value	EPDM	weight
(mm)	(mm)		(l/min)	Code	(kg)
110	100	10	6500	138 567 214	13.320
140	125	10	11500	138 567 216	18.650
160	150	10	16500	138 567 217	22.346
225	200	10	39600	138 567 220	36.037

d	D	D1	D2	L	L1	L2	L3	H	H1	H2	H3	z	z1	z2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
110	310	188	168	552	72	179	122	460	104	167	190	696	320	56
140	280	233	222	670	84	172	179	475	119	173	183	830	383	64
160	358	259		720	90	179	122	535	143	203	190	895	412	72
225	409	325		776	110	179	122	580	170	210	200	996	462	73

d	closest inch
(mm)	(inch)
110	4
140	5
160	6
225	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>