



Stress Less Valve Support

- Designed to properly support GF valves when the connected piping moves, due to thermal expansion and contraction. Smooth linear movement (± 3 in) with very low friction. Helps ensure the full design life of piping systems by eliminating stress points.
- For GF metric and IPS valves with integrated support bases. Types 546, 523, 543 horizontal and 5-series diaphragm valves. Manual and actuated.
- Sizes 3/8" – 2" (16mm – 63mm).
- Can be mounted on any flat surface or strut support (shown in image, valve not included).
- Valve support includes base made of glass-filled PP, and upper slider made of PP. Both are black and UV resistant.
- Supplied with 2 stainless steel hex socket screws for mounting valve to upper slider component.

Size (mm)	Inch (inch)	Code	H (mm)	w (mm)	L (mm)
16 - 32	3/8 - 1	155 484 120	43	52	160
40 - 63	1 1/4 - 2	155 484 121	33	85	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>