





PROGEF Standard Ball valve type 546 Pro
With fusion sockets PP-H ISO
With spring return unit

Model:

- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- Z-dimension, valve end and union nut **are compatible** with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (dp=1 bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	3/8	10	71	167 546 361	1	0.119	167 546 371	1	0.115
20	15	1/2	10	185	167 546 362	1	0.120	167 546 372	1	0.123
25	20	3/4	10	350	167 546 363	1	0.188	167 546 373	1	0.184
32	25	1	10	700	167 546 364	1	0.256	167 546 374	1	0.258

B3 (mm)	DE1 (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
25	50	M6	60.5	27	12	93	28	82	35	47	67
25	50	M6	60.5	27	12	95	28	82	35	47	66
25	58	M6	74.0	30	12	109	33	106	44	62	76
25	68	M6	80.0	36	12	119	36	106	44	62	82

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>