



MSE 63/MSE 110 Socket fusion tool

- For fusion jointing of PP and PE pipes and fittings
- Electronic temperature control
- Support for heating bushes and spigots of d 16 to 63 mm (110 mm)
- Pick up for floor stand or table clamp
- Monitoring and setting of heating element temperature
- High temperature accuracy over the entire heating surface
- The 115 V type is available both in the version with plug (US standard NEMA 5-15P) and in the version without plug, to make possible for the customer to assemble any other type of plug, compatible with the tool technical specifications, under his own responsibility.

d-d (mm)	Type	Performance	Code	Weight (kg)
16 - 63	MSE 63 E with Schuko plug	230 V/800 W	790 105 082	1.800
16 - 63	MSE 63 E without plug	115 V/800 W	790 105 097	2.145
16 - 63	MSE 63 E with US plug	115 V/800 W	790 105 164	2.200
16 - 110	MSE 110 E with Schuko plug	230 V/1500 W	790 105 084	3.200
16 - 110	MSE 110 E without plug	115 V/1500 W	790 105 127	3.200
16 - 110	MSE 110 E with US plug	115 V/1500 W	790 105 175	3.250

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>