



Positioner RPC D, RPC PID- Modbus TCP For single-/double-acting pneumatic rotary actuators

Model:

- For pneumatic rotary actuators in single-acting and double-acting function
- Operation and configuration via integrated display
- Supply voltage 24V DC
- Setpoint control via Modbus TCP
- Position feedback via Industrial Modbus TCP
- Conductive plastic rotary potentiometer as position sensor
- Protection class IP65/IP67
- 1 digital input, galvanically isolated, PNP
- Operating mode indication (automatic / manual)
- Approved and listed according to cULus

Option:

- Mounting kit for pneumatic actuator installation, not included in scope of supply (199190647)
- Suitable connection cables are available separately as accessories.

Description	Code	Weight (kg)	Y4 (mm)	W1 (mm)	W2 (mm)	L1 (mm)	L2 (mm)
RPC D Modbus TCP	199 190 635	1.000	83.5	48	62	60.5	100.5
RPC PID Modbus TCP	199 190 636	1.000	83.5	48	62	60.5	100.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>