



SOCKET FUSION COUPLING MALE THREAD GEOTHERMAL TRANSITIONS: PE4710, MPT x IPS

- Approval: ASTM D2513
- Approval: ASTM D2683
- Approval: ANSI B1.20.1
- Call for availability of other sizes and dimensions.
- GF Central Plastics offers thousands of different riser configurations. The configurations listed here are standard stocking sizes.

Size	GF Code	weight (lb)	L (inch)	L2 (inch)	z (inch)	z2 (inch)	Minimum Or- der Qty
0.75" MPT x 0.75" IPS	360 001 608	0.4	3.30	1.11	1.44	0.75	60
0.75" MPT x 1" IPS	360 001 609	0.4	3.00	1.02	1.23	0.75	40
0.75" MPT x 1.25" IPS	360 001 610	0.4	3.20	1.02	1.43	0.75	25
1" MPT x 1" IPS	360 001 613	0.7	3.50	1.31	1.32	0.88	35
1" MPT x 1.25" IPS	360 001 614	0.7	3.60	1.33	1.40	0.88	25
1.25" MPT x 1.25" IPS	360 001 616	0.9	3.60	1.41	1.32	0.88	25
1.5" MPT x 1.5" IPS	360 001 618	1.1	3.70	1.51	1.23	0.96	20
2" MPT x 2" IPS	360 001 619	1.9	4.00	1.64	1.36	1.00	12

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>