



MULTI/JOINT® 3207 Plus Wide Range end cap blind, restraint, Uni/Fiksers

Model:

- Suitable for all kinds of pipe material
- Suitable for water and gas (EPDM only for potable water)
- Ductile iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- Hygiene protection included DN50 - DN1025

Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- * DN350 & DN400 for plastic pipe materials = PN 10 bar water / MOP 5 bar gas

Note:

ID min. = minimum insertion depth

DN (mm)	Range 1 (mm)	NBR / A2 Code	Weight (kg)	EPDM / A2 Code	Weight (kg)
50	46 - 71	709 375 210	3.200	709 375 610	3.200
65	63 - 90	709 375 212	4.400	709 375 612	4.400
80	84 - 105	709 375 214	5.000	709 375 614	5.000
100	104 - 132	709 375 216	5.900	709 375 616	5.900
125	132 - 155	709 375 218	7.900	709 375 618	7.900
150	154 - 192	709 375 220	10.900	709 375 620	10.900
200	192 - 232	709 375 224	17.500	709 375 624	17.500
225	230 - 268	709 375 226	23.100	709 375 626	23.100
250	267 - 310	709 375 228	27.700	709 375 628	27.700
300	315 - 356	709 375 232	34.100	709 375 632	34.100
400	392 - 433	709 375 234	45.100	709 375 634	45.100

DN (mm)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	709 375 010	709 375 310	3.200
65	709 375 012	709 375 312	4.400
80	709 375 014	709 375 314	5.000
100	709 375 016	709 375 316	5.900
125	709 375 018	709 375 318	7.900
150	709 375 020	709 375 320	10.900
200	709 375 024	709 375 324	17.500
225	709 375 026	709 375 326	23.100
250	709 375 028	709 375 328	27.700
300	709 375 032	709 375 332	34.100
400	709 375 034	709 375 334	45.100

DN (mm)	Min. (mm)	Max. (mm)	b ID min. (mm)	number of Bolts	e (mm)	PN Water (bar)	MOP Gas (bar)	
50	125	147	170	84	3	M12	16	8
65	133	156	191	84	3	M12	16	8
80	135	157	210	84	3	M12	16	8
100	143	169	241	90	3	M16	16	8
125	149	172	270	90	4	M16	16	8
150	169	206	312	110	4	M16	16	8
200	183	220	371	110	6	M16	16	8

Data sheet

valid from: 6/17/25



DN	Min.	Max.	b	ID min.	number of	e	PN Water	MOP Gas
(mm)	(mm)	(mm)	(mm)	(mm)	Bolts	(mm)	(bar)	(bar)
225	216	254	415	125	6	M20	16	8
250	225	268	445	130	6	M20	16	8
300	238	276	495	130	8	M20	16	8
400	261	303	580	135	10	M20	16*	8*

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>