



Signet 2744-2747 DryLoc[°] Differential pH/ORP Electrodes

pH/ORP:

- Differential design for stable measurements in the most aggressive applications
- Long service life even in severe or difficult chemical applications
- Memory chip enabled for access to a wide range of unique features when connected to the Signet 2751 pH/ORP Smart Sensor Electronics
- High performance glass that can withstand high pH caustic media as well as elevated temperature applications
- Ryton[®](PPS) body and PTFE junction for broad range of chemical compatibility
- Compatible with all Signet instruments

MFR #	Electrode Type	Style	Temperature Compensation	Compatible Preamplifier	Mounting	Code
3-2744-1	рН	Flat	ЗК	2751 Smart Sensor Elec- tronics	with threaded connection	159 001 944
3-2744-2	рН	Flat	PT1000	2751 Smart Sensor Elec- tronics	with threaded connection	159 001 910
3-2746-1	рH	Bulb	ЗК	2751 Smart Sensor Elec- tronics	with threaded connection	159 001 911
3-2746-2	рH	Bulb	PT1000	2751 Smart Sensor Elec- tronics	with threaded connection	159 001 912

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com