



## Positioner Type SPC D, Type SPC PID, for single-acting stroke actuators with Industrial Ethernet

### Model:

- For pneumatic linear actuators in single-acting function
- Operation/configuration via DIP switch internal
- Supply voltage 24V DC
- Control of position via Industrial Ethernet
- Contactless (wear-free) analog inductive position sensor
- Electrical connection multi-pin plug (not included)
- Protection class IP65/IP67
- Binary input (fail-safe position, changeover)
- Operating status (automatic / manual)
- Position feedback via Industrial Ethernet
- Approved and listed according to cULus

### Option:

- Adaption for mounting on pneumatic actuator
- Multipole plug for supply voltage, not for Industrial Ethernet

| Description          | Code               | Weight<br>(kg) | Y4<br>(mm) | Lmax<br>(mm) | Wmax<br>(mm) |
|----------------------|--------------------|----------------|------------|--------------|--------------|
| SPC D PROFINET       | <b>199 190 623</b> | 0.690          | 158.5      | 117.5        | 99.5         |
| SPC D Ether-Net/IP   | <b>199 190 624</b> | 0.690          | 158.5      | 117.5        | 99.5         |
| SPC D Modbus TCP     | <b>199 190 633</b> | 0.690          | 158.5      | 117.5        | 99.5         |
| SPC PID PROFINET     | <b>199 190 626</b> | 0.690          | 158.5      | 117.5        | 99.5         |
| SPC PID Ether-Net/IP | <b>199 190 627</b> | 0.500          | 158.5      | 117.5        | 99.5         |
| SPC PID Modbus TCP   | <b>199 190 634</b> | 0.500          | 158.5      | 117.5        | 99.5         |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>