



Swing Fork Level Switch 2280 Cable/DIN Connectors, PNP/NPN/2-Wire

- Vibrating Principle
- Sensor body: Stainless Steel 1.4571
- Switching Function: 2-wire AC; 3-wire PNP-NPN
- Power Supply: 12...55 V DC or 20...255 V AC, 50/60 HZ
- Connection: Cable PVC 5x0.5mm², 3m or DIN Connector

MFR #	Length (mm)	Process Con- nection	Connection	Code
2280- S-5WBO-1	69	1" BSP	DIN Connector	159 300 200
2280- S-5WBC-1	69	1" BSP	Cable	159 300 201
2280- S-5WBO-2	125	1" BSP	DIN Connector	159 300 202
2280- S-5WBC-2	125	1" BSP	Cable	159 300 203
2280- S-5WNO-1	69	1" NPT	DIN Connector	159 300 220
2280- S-5WNC-1	69	1" NPT	Cable	159 300 221
2280- S-5WNO-2	125	1" NPT	DIN Connector	159 300 222
2280- S-5WNC-2	125	1" NPT	Cable	159 300 223



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>