



Ductile cast iron saddle female thread (Rp)

- Use: Drinking water and waste water system
- Temp: - 5°C to + 50°C
- Pressure rating: 16 bar
- Seal type: EPDM
- Hardness: Class70
- Female thread: ISO 7
- Belt type: Bottom belt with NBR protection rubber

1/2" Code	Weight (kg)	GP	3/4" Code	1" Code	1 1/4" Code
300 216 621	1.490	4	300 216 624	300 216 627	300 216 615
300 216 622	1.550	4	300 216 625	300 216 628	300 216 616
300 216 623	2.340	4	300 216 626	300 216 629	300 216 617
300 216 630	2.460	4	300 216 633	300 216 636	300 216 618
300 216 631	2.560	4	300 216 634	300 216 637	300 216 619
300216632	2.750	4	300 216 635	300 216 638	300 216 620

L 1/2" to 1 1/4" (mm)	L1 1/2" to 1 1/4" (mm)	L 2" & 2 1/2" (mm)	L1 2" & 2 1/2" (mm)	d (inch)
172.5	122.5			3#
172.5	122.5			4#
172.5	122.5	190	136	6#
172.5	122.5	190	136	8#
172.5	122.5	190	136	10#
172.5	122.5	190	136	12#

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>