

Data sheet


valid from: 12/11/22



ABS Line strainer type 305 With solvent cement spigots metric

Model:

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- Overall length EN 558
- Cylindrical screen must be ordered separately
- Screen in stainless steel operable temperature range up -40°C to +60°C
- Screen in PVC-U operable temperature range up 0°C to +60°C



d (mm)	PN (bar)	EPDM Code	SP	Weight (lb)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
20	10	169 305 302	1	0.179	48	65	124	130	28	1/2
25	10	169 305 303	1	0.265	54	76	144	150	37	3/4
32	10	169 305 304	1	0.397	62	90	154	160	37	1
40	10	169 305 305	1	0.626	71	104	174	180	44	1 1/4
50	10	169 305 306	1	1.067	88	124	194	200	48	1 1/2
63	10	169 305 307	1	1.720	103	148	224	230	60	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>