



COOL-FIT PE Plus Reducer, d280-d450

Model:

- Pre-insulated PE100 **SDR17**, metric
- Insulation made from PUR foam
- Outer jacket impact and UV resistant. Color: Black
- Type B: Spigot fitting with free ends (Electrofusion Coupler needed for joining)

D1	SDR	PN	Code	weight	L	L1	z	Type	closest inch
(mm)		(bar)		(kg)	(mm)	(mm)	(mm)		(inch)
315	17	10	738 903 825	2.800	123	110	332	B	10
315	17	10	738 903 829	4.700	126	110	335	B	10
355	17	10	738 903 830	5.100	133	110	365	B	10
315	17	10	738 903 836	7.100	126	110	340	B	12
355	17	10	738 903 837	7.400	133	123	365	B	12
400	17	10	738 903 838	6.800	133	126	365	B	12
355	17	10	738 903 844	8.200	148	123	390	B	14
400	17	10	738 903 845	7.700	148	126	390	B	14
450	17	10	738 903 846	8.300	148	133	390	B	14
400	17	10	738 903 853	9.100	150	126	415	B	16
450	17	10	738 903 854	11.400	150	133	420	B	16
500	17	10	738 903 855	11.000	150	148	405	B	16
400	17	10	738 903 862	13.200	165	126	390	B	18
450	17	10	738 903 863	13.600	165	133	390	B	18
500	17	10	738 903 864	13.700	165	148	393	B	18
560	17	10	738 903 865	14.800	165	150	395	B	18

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>