



## INSTAFLEX Vanne d'arrêt BTV 2 Avec manchon G 1/4" pour vidange

- Matériau: PB, laiton, bronze
- Laiton: Faible teneur en plomb
- Connection: Soudage dans l'emboîture, sans robinet de vidange 1/4"
- Pression de service: 16 bars
- Homologations: Approuvé pour l'eau chaude et froide
- Gasket: EPDM, quality for potable water
- \* jusqu'à épuisement du stock

|   | d<br>(mm) | Code        | CAN     | SP | Poids<br>(kg) |
|---|-----------|-------------|---------|----|---------------|
| * | 20        | 761 070 310 | 481 752 | 1  | 0.443         |
| * | 25        | 761 070 311 | 481 753 | 1  | 0.434         |
| * | 32        | 761 070 312 | 481 754 | 1  | 0.434         |
| * | 40        | 761 070 313 | 481 755 | 1  | 1.161         |
| * | 50        | 761 070 314 | 481 756 | 1  | 1.213         |
| * | 63        | 761 070 315 | 481 757 | 1  | 1.394         |

|   | d<br>(mm) | D<br>(mm) | L<br>(mm) | H<br>(mm) | z<br>(mm) | Valeur (Zeta) | Valeur kv 100<br>(Δp=1 bar)<br>(l/min) |
|---|-----------|-----------|-----------|-----------|-----------|---------------|----------------------------------------|
| * | 20        | 55        | 40        | 112       | 25        | 0.4           | 421                                    |
| * | 25        | 55        | 40        | 112       | 22        | 0.4           | 421                                    |
| * | 32        | 55        | 43        | 112       | 23        | 0.4           | 421                                    |
| * | 40        | 90        | 55        | 165       | 33        | 0.3           | 1291                                   |
| * | 50        | 90        | 60        | 165       | 35        | 0.3           | 1291                                   |
| * | 63        | 90        | 75        | 165       | 47        | 0.3           | 1291                                   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>