



## Elbow 90° PVDF/PE100

\* Inner pipe: SYGEF Select PVDF-E

| d<br>(mm) | D<br>(mm) | PN<br>(bar) | PN<br>(AL)<br>(bar) | SDR | Code        | PVDF-E *<br>Code | Weight<br>(kg) |
|-----------|-----------|-------------|---------------------|-----|-------------|------------------|----------------|
| 20        | 50        | 16          | 16                  | 21  | 735 104 206 | 735104206E       | 0.470          |
| 25        | 50        | 16          | 16                  | 21  | 735 104 207 | 735104207E       | 0.496          |
| 32        | 63        | 16          | 16                  | 21  | 735 104 208 | 735104208E       | 0.837          |
| 40        | 75        | 16          | 16                  | 21  | 735 104 209 | 735104209E       | 1.339          |
| 50        | 90        | 16          | 10                  | 21  | 735 104 210 | 735104210E       | 2.069          |
| 63        | 110       | 16          | 10                  | 21  | 735 104 211 | 735104211E       | 3.421          |
| 75        | 125       | 16          | 10                  | 21  | 735 104 212 | 735104212E       | 5.113          |
| 90        | 140       | 16          | 10                  | 21  | 735 104 213 | 735104213E       | 9.390          |
| 110       | 160       | 16          | 10                  | 21  | 735 104 214 | 735104214E       | 10.360         |
| 125       | 180       | 10          | 10                  | 33  | 735 104 265 | 735104265E       | 14.591         |
| 140       | 200       | 10          | 10                  | 33  | 735 104 266 | 735104266E       | 16.531         |
| 160       | 225       | 10          | 10                  | 33  | 735 104 267 | 735104267E       | 23.713         |
| 200       | 280       | 10          | 10                  | 33  | 735 104 269 | 735104269E       | 39.186         |
| 225       | 315       | 10          | 10                  | 33  | 735 104 270 | 735104270E       | 44.782         |

| d<br>(mm) | D1<br>(mm) | ZA 1<br>(mm) | ZA 2<br>(mm) | L1<br>(mm) | Zi 1<br>(mm) | Zi 2<br>(mm) |
|-----------|------------|--------------|--------------|------------|--------------|--------------|
| 20        | 66         | 105          | 175          | 71         | 125          | 195          |
| 25        | 66         | 105          | 175          | 71         | 125          | 195          |
| 32        | 81         | 120          | 190          | 81         | 140          | 210          |
| 40        | 97         | 145          | 225          | 94         | 165          | 245          |
| 50        | 118        | 170          | 260          | 122        | 190          | 280          |
| 63        | 139        | 210          | 310          | 147        | 230          | 330          |
| 75        | 161        | 225          | 330          | 155        | 245          | 350          |
| 90        | 196        | 265          | 375          | 191        | 285          | 395          |
| 110       | 196        | 275          | 390          | 191        | 295          | 410          |
| 125       | 234        | 295          | 415          | 210        | 315          | 435          |
| 140       | 251        | 300          | 420          | 185        | 320          | 440          |
| 160       | 281        | 350          | 475          | 220        | 370          | 495          |
| 200       | 316        | 410          | 550          | 265        | 430          | 570          |
| 225       | 316        | 400          | 550          | 245        | 420          | 570          |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>