



Analytical Threaded Sensor, PN 16 PVDF-HP

IR Plus/BCF Plus Fusion

d (mm)	Suitable for	FM	SDR	Code	e (mm)	L (mm)	L1 (mm)	L2 (mm)
50	FNPT 1/4 inch	BCF, IR	21	735 991 840	3.0	135	58	77
50	FNPT 1/2 inch	BCF, IR	21	735 991 841	3.0	135	58	77
50	FNPT 3/4 inch	BCF, IR	21	735 991 842	3.0	135	58	77
50	FNPT 1 inch	BCF, IR	21	735 991 843	3.0	135	58	77
63	FNPT 1/4 inch	BCF, IR	21	735 991 844	3.0	151	66	85
63	FNPT 1/2 inch	BCF, IR	21	735 991 845	3.0	151	66	85
63	FNPT 3/4 inch	BCF, IR	21	735 991 846	3.0	151	66	85
63	FNPT 1 inch	BCF, IR	21	735 991 847	3.0	151	66	85
75	FNPT 1/4 inch	BCF, IR	21	735 991 848	3.6	165	75	90
75	FNPT 1/2 inch	BCF, IR	21	735 991 849	3.6	165	75	90
75	FNPT 3/4 inch	BCF, IR	21	735 991 850	3.6	165	75	90
75	FNPT 1 inch	BCF, IR	21	735 991 851	3.6	165	75	90
90	FNPT 1/4 inch	BCF, IR	21	735 991 852	4.3	188	90	98
90	FNPT 1/2 inch	BCF, IR	21	735 991 853	4.3	188	90	98
90	FNPT 3/4 inch	BCF, IR	21	735 991 854	4.3	188	90	98
90	FNPT 1 inch	BCF, IR	21	735 991 855	4.3	188	90	98
110	FNPT 1/4 inch	BCF, IR	21	735 991 856	5.3	219	110	109
110	FNPT 1/2 inch	BCF, IR	21	735 991 857	5.3	219	110	109
110	FNPT 3/4 inch	BCF, IR	21	735 991 858	5.3	219	110	109
110	FNPT 1 inch	BCF, IR	21	735 991 859	5.3	219	110	109

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>