





NeoFlow Pressure Sustaining Valve POM-C
DN50 - DN150 / Set pressure range 14.5 - 232 psi [g]


- Nominal pressure: PN16
- Connection type: Wafer Design
- Sealing material: EPDM
- Body material: POM-C
- Components: Stainless Steel
- Thread fittings: NPT
- Medium: Water
- Co-developed with OFUI



d	DN	PN	min Pressure	max Pressure	Body	Code	Weight
(mm)	(mm)	(bar)	(psi)	(psi)			(lb)
63	50	16	14.5	232.0	POM-C	193 174 311	127.9
90	80	16	14.5	232.0	POM-C	193 174 313	147.7
110	100	16	14.5	232.0	POM-C	193 174 314	178.6
160	150	16	14.5	232.0	POM-C	193 174 317	291.0



D	Lmax	Lb	Hmax	Wmax
(inch)	(inch)	(inch)	(inch)	(inch)
4.13	10.47	4.76	11.42	10.83
5.28	11.38	5.31	12.20	11.61
6.38	11.30	6.10	13.39	12.20
8.58	11.38	9.06	15.55	13.98



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>