



installatiefitting type 312 PVC-U metrisch klemzadel

Uitvoering:

- zadel met draadaansluiting 5/4" NPSM
- zadelbovendeel verlijmbaar
- afdichting: lippenafdichting uit EPDM

toepassing:

- compatibel met Signet flowsensoren: type 2551, 2537, 515, 8510, 2536, 8512
- compatibel met Signet pH/ORP sensoren: type 2724, 2725, 2726, 2736, 2735

let op:

- de sensorlengte is afhankelijk van de installatiefitting

d (mm)	DN (mm)	PN	code	SP	gewicht (kg)	sensor type	H (mm)	L (mm)
75	65	16	198 150 538	1	0,780	flow X0, pH XX	99	105
90	80	16	198 150 539	1	0,835	flow X0, pH XX	105	105
110	100	16	198 150 540	1	0,885	flow X0, pH XX	114	105
160	150	16	198 150 543	1	1,375	flow X1	157	120
225	200	16	198 150 545	1	1,700	flow X1	184	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>