



ecoFIT Segmented Bend 1.5D 60° PE100 SDR11

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 12.8 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2316606090	1.06	254	150	180.0	8.2	
110	P2316606110	1.86	302	200	176.0	10.0	
125	P2316606125	2.49	308	200	187.5	11.4	
140	P2316606140	3.21	321	200	210.0	12.7	
160	P2316606160	4.41	339	200	240.0	16.6	
180	P2316606180	5.92	356	200	270.0	16.4	
200	P2316606200	7.62	373	200	300.0	18.2	
225	P2316606225	10.18	395	200	337.5	20.5	
250	P2316606250	14.82	467	250	375.0	22.7	
280	P2316606280	19.61	493	250	420.0	25.4	
315	P2316606315	31.36	623	350	472.5	28.6	
355	P2316606355	42.11	657	350	532.5	32.2	
400	P2316606400	56.43	696	350	600.0	36.3	
450	P2316606450	75.71	740	350	675.0	40.9	
500	P2316606500	105.26	833	400	750.0	45.4	
560	P2316606560	140.11	885	400	840.0	50.8	
630	P2316606630	199.46	996	450	945.0	57.2	
710	P2316606710	283.89	1115	500	1065.0	64.5	
*	800	P2316606800	435.43	1343	650	1200.0	72.6
*	900	P2316606900	606.91	1679	700	1350.0	81.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:

info.ps@georgfischer.com Internet: <http://www.gfps.com>