


Data sheet

valid from: 7/26/17



Installation fitting type 310 ABS metric

Model:

- Threaded outlet 1 1/4" NPSM
- With solvent cement socket metric
- Material: ABS

Range of use:

- compatible signet pH/ORP sensors: type 2724, 2725, 2726
- compatible signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

Attention:

- sensor length depends on installation fitting

DN (mm)	d (mm)	PN (bar)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	Sensor Type	D (mm)	H (mm)	L (mm)
20	25	10	729 310 007	1	0.100	3/4	32	flow X0, pH XX	35	78	100
25	32	10	729 310 008	1	0.143	1	33	flow X0, pH XX	44	81	110
32	40	10	729 310 009	1	0.140	1 1/4	29	flow X0, pH XX	51	85	110
40	50	10	729 310 010	1	0.187	1 1/2	29	flow X0, pH XX	63	89	120
50	63	10	729 310 011	1	0.257	2	28	flow X0, pH XX	78	95	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>