



ecoFIT Segmented Bend 22.5° PE100 SDR13.6

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**

Note:

* Please call us for availability

d (mm)	Code	Weight (kg)	Z (mm)	L (mm)	R (mm)	e (mm)
90	P2315603090	0.62	177	150	135.0	6.7
110	P2315603110	1.25	233	200	165.0	8.1
125	P2315603125	1.61	237	200	187.5	9.2
140	P2315603140	2.06	242	200	210.0	10.3
160	P2315603160	2.80	248	200	240.0	11.8
180	P2315603180	3.62	254	200	270.0	13.3
200	P2315603200	4.53	260	200	300.0	14.7
225	P2315603225	5.86	267	200	337.5	16.6
250	P2315603250	8.86	325	250	375.0	18.4
280	P2315603280	11.44	334	250	420.0	20.6
315	P2315603315	19.26	444	350	472.5	23.2
355	P2315603355	24.97	456	350	532.5	26.1
400	P2315603400	32.71	469	350	600.0	29.4
450	P2315603450	42.76	484	350	675.0	33.1
500	P2315603500	59.83	549	400	750.0	36.8
560	P2315603560	77.10	567	400	840.0	41.2
630	P2315603630	110.39	638	450	945.0	46.3
710	P2315603710	155.59	712	500	1065.0	52.2
800	P2315603800	247.38	889	650	1200.0	58.8
900	P2315603900	341.58	969	700	1350.0	66.1
* 1000	P2315603001	428.90	998	700	1500.0	73.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>