



Tapping Saddle with GF Branch Saddle Topload Applikation: Gas supply (10 bar)

Tapping-T: PE100 SR11 (EN 1555-3)

Body, Body Cap, Sleeve: Steel ST-52 + Bichromated

Pin: Steel F212 + Bichromated

Cutter: Steel F-125


O-Rings: EPDM-Rubber (EN 681-1)

Tapping Saddle: PE 100 SDR11 (ISO S5)

* Outlet d 160 to 225 mm, main pipe 315 to 630 mm, delivered without lower part, , installation only with installation set Topload TL225 (799.300.807), Angle adaptors (799.350.340) for fusion cable required

Remark:

Tappings saddles are pre-assembled. Outlet d 160 mm is electro fused, outlet d 225 mm is butt fused, to be declared with order.



d (mm)	d1 (mm)	Code	SP	Weight (kg)	H1 (mm)	z (mm)	L (mm)	d2 (mm)	Type
315	160	200 011 099	1	19.548	199	206	508	115	B
355	160	200 011 100	1	19.348	199	206	508	115	B
400	160	200 011 101	1	19.623	199	206	508	115	B
315	225	200 011 102	1	24.508	286	270	591	160	A
355	225	200 011 103	1	24.594	286	270	591	160	A
400	225	200 011 104	1	24.612	286	270	591	160	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>