



JRG Sanipex MT Reduction inlet for t-piece insulation boxes EPP

- Description: Half shells made of EPP for an easy, professional and economical insulation of JRG Sanipex MT fittings
- Material: Expanded polypropylene (EPP)
- Temperature: max. 110°C
- Thermal conductivity: 0.035 W/mK according EN 12667
- Building material class: B2 according DIN 4102 and E according EN 13501-1

d1 (mm)	d (mm)	JRG Code	GF Code	PF	SP	Weight (kg)	d2 (mm)	d3 (mm)	l (mm)	l1 (mm)
20	16	4730.500	351 620 671	2 J3 J74 001	20	0.001	30	35	34	24
26	16	4730.502	351 626 671	2 J3 J74 001	20	0.002	37	45	43	29
26	20	4730.504	351 626 672	2 J3 J74 001	20	0.001	37	45	43	29
32	16	4730.506	351 632 671	2 J3 J74 001		0.002	44	54	53	34
32	20	4730.508	351 632 672	2 J3 J74 001	20	0.001	44	54	53	34
32	26	4730.510	351 632 673	2 J3 J74 001	20	0.001	44	54	53	34
40	26	4730.516	351 640 671	2 J3 J74 001	20	0.004	53	66	62	39
40	32	4730.518	351 640 672	2 J3 J74 001	0	0.003	53	66	62	38
50	26	4730.524	351 650 671	2 J3 J74 001	0	0.009	66	78	76	46
50	32	4730.526	351 650 672	2 J3 J74 001	0	0.008	66	78	76	46
50	40	4730.528	351 650 673	2 J3 J74 001	0	0.005	66	78	76	46
63	26	4730.534	351 663 671	2 J3 J74 001	0	0.021	82	97	96	59
63	32	4730.536	351 663 672	2 J3 J74 001	0	0.019	82	97	96	59
63	40	4730.538	351 663 673	2 J3 J74 001	0	0.015	82	97	96	59
63	50	4730.540	351 663 674	2 J3 J74 001	0	0.010	82	97	96	59

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>