



PROGEF Standard Ball valve type 180
24V
With manual emergency override
With butt fusion spigots PP-H SDR11 ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	SDR	EPDM Code	FKM Code	Weight (kg)
20	15	½	10	185	11	199 180 363	199 180 373	2.100
25	20	¾	10	350	11	199 180 364	199 180 374	2.200
32	25	1	10	700	11	199 180 365	199 180 375	2.300
40	32	1 ¼	10	1000	11	199 180 366	199 180 376	2.600
50	40	1 ½	10	1600	11	199 180 367	199 180 377	3.000
63	50	2	10	3100	11	199 180 368	199 180 378	3.800
75	65	2 ½	10	5000	11	199 180 369	199 180 379	6.200
90	80	3	10	7000	11	199 180 370	199 180 380	7.200
110	100	4	10	11000	11	199 180 371	199 180 381	11.200

d (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	s1 (mm)	L (mm)	L1 (mm)	Actuator	B3 (mm)
20	50	122	M6	227	27	12	28	180	97	83	1.9	130	33	EA25	25
25	58	122	M6	231	30	12	33	180	97	83	2.3	143	33	EA25	25
32	68	122	M6	237	36	12	36	180	97	83	3.0	150	33	EA25	25
40	84	122	M8	243	44	15	43	180	97	83	3.7	171	33	EA25	45
50	97	122	M8	249	51	15	45	180	97	83	4.6	191	33	EA25	45
63	124	122	M8	264	64	15	51	180	97	83	5.8	220	33	EA25	45
75	166	122	M8	313	85	15	68	180	98	82	8.2	266	33	EA45	70
90	200	122	M8	325	105	15	71	180	98	82	10.0	264	33	EA45	70
110	238	122	M12	363	123	22	82	180	98	82	12.0	301	33	EA120	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 4/7/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>